

## Quick Check® PC600 Bar Code Symbol Verifier



### Features

Easy Microsoft® Windows® 98, Windows® XP, Windows® 2000, or Windows NT® Set-Up and Operation

Interchangeable Optical Input Devices

Test all Major Symbolologies Against ISO/IEC or Traditional Parameters

Test UCC/EAN-128

Save Files as Data Files and/or ASCII Text Files

The Quick Check PC600 Verifier is a professional, quality control tool for verifying the readability and standards compliance of printed bar codes. It consists of a Windows-based software package, a "mouse" wand or pen wand bar code optical sensing device, and an interface that connects to the serial port of an IBM®-compatible desktop or laptop PC.

For printing, receiving, or using bar codes in manufacturing or distribution applications, the Quick Check PC600 Verifier provides quick and easy-to-view full ISO/IEC test parameter analysis and traditional pass/fail parameters. The QCPC600 is manufactured and traceable to NIST (National Institute of Standards and Technology) standards developed by the Uniform Code Council (UCC) and Automatic Identification Manufacturers (AIM).

Input is provided by either an interchangeable mouse wand or pen wand that is compatible with Quick Check 600 or 800 Series Desktop Verifiers. To accommodate varying label densities, just select the appropriate aperture; in mouse wands choose from 3, 5, 6, 10, and 20 mil sizes; in pen wands choose from 5, 6, and 10 mil sizes. Each unit decodes and verifies the character format for Code 39, Interleaved 2 of 5, EAN/UPC, Codabar, Code 128, Telepen, and UCC/EAN-128. The Quick Check PC600 Verifier delivers information about the critical optical characteristics of bar codes including:

- All ISO/IEC bar code print quality parameters
- All traditional bar code print quality parameters

*Other Features Include:*

- Unrecognized symbols mode to evaluate the hardest to read bar codes
- Fully functional reflectometer mode
- Display and printability of bar/space element histogram with element width averages and ranges
- Parsing of UCC/EAN-128 message with application identifiers described

Because the Quick Check PC600 Verifier operates on your PC, it offers many advantages not available from standalone units. Bar code quality information is displayed directly on your computer monitor and hard copy output can be produced on any local or network printer. Automatic ISO/IEC symbol grade calculation provides instant bar code quality feedback. Easy-to-follow menus guide the user through the entire verification process, providing more detailed results such as scan reflectance profiles with highlighted defect, decodability, and minimum edge contrast. Once obtained, test results can even be shared with other Windows applications or stored for later retrieval. The Quick Check PC600 Verifier has all the power and flexibility you need to ensure strict bar code standards compliance.

Upgrade your image.



# Quick Check® PC600 Specifications

## Mechanical

### Standard Hardware

<b>Configuration:</b>	Interface/Input Box, power supply, and choice of mouse scanner, available in aperture sizes of 03, 05, 06, 10, 20 mils, or pen wand in 05, 06, and 10 mils. (Choose visible or infrared for either input device.) Plugs into PC serial port
<b>Optical Input Connector:</b>	9-pin plastic squeeze-to-release male Allows input from any existing or potential future HHP interchangeable scanner (excluding laser)
<b>I/O Connector:</b>	6-pin modular Allows for I/O communications with computer
<b>Power Connector:</b>	Power jack for powering input device and interface electronics Uses existing HHP QCAC charger

## Environmental

<b>Operating Temperature:</b>	32 to 122° F (0 to 50° C)
<b>Storage Temperature:</b>	14 to 158° F (-20 to 70°C)
<b>Relative Humidity:</b>	5% to 95% Non-condensing
<b>ESD Sensitivity:</b>	Withstands 20 attempts to discharge 15Kv to the unit
<b>Sealability:</b>	Meets NEMA 1
<b>Shock:</b>	3 feet (91 cm) to concrete

## Software

<b>Verification Modes:</b>	RL, RD, print contrast signal ISO/IEC reflectance parameters Bar/Space dimensional measurement Average bar growth/shrinkage ISO/IEC decodability ISO/IEC 10-scan grade averaging Wide-To-Narrow ratio measurements Scan profiles on CRT and printer output Fixed message length testing "X" dimension calculation Scan speed variation indication Variable or ISO/IEC symbol grade averaging Storage of scan results and scan profiles Ability to add notations to scan file for later retrieval
----------------------------	---

**Programming Procedures:** Report generator allows choice of print format. Click directly on a parameter to configure its setting

**Verification Methods:** Parameters determined by the ISO/IEC print quality standard or traditional pass/fail criteria

**Result Indications:** Visual, using an efficient graphical display  
Audible using the PC speaker

**Display Organization:** Symbol Grade with Running Average  
Scan Grade  
Symbology and Symbol Data  
Reflectance measurements, including RL, RD, Print Contrast, Rmin/Rmax, Minimum Edge, Contrast, Modulation, and Defects  
Format parameters, including Check Digit and Message Length  
Dimensional results, including Decodability, Intercharacter gap, Wide-To-Narrow Ratio, and Average Bar Error  
Additional results and errors are available in a scrolling list

**Symbologies Verified** Code 39 (1 to 49 characters); Interleaved 2 of 5 (2 to 78 characters); EAN/UPC (-A, -E, -8 and -13) includes magnification settings in a maximum of 16 steps consisting of: 80, 85, 90, 95, 100, 105, 110, 115, 120, 125, 130, 140, 150, 160, 180 and 200%; Codabar (1 to 61 characters); Code 128 (1 to 70 characters); Telepen

**Applications:** UCC/EAN-128

**Safety/Regulatory** FCC Class A, CE

IBM is a registered trademark of International Business Machines, Inc.  
Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries.



### System Requirements

- Windows 98, 2000, or Windows NT operating system
- PC (or compatible) with 486 or better processor
- 4 MB of RAM
- 3 MB available on hard drive
- Available COM Port (COM 1-4)
- Microsoft®-compatible mouse

## Worldwide Offices

**Offices Serving North America**  
Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America: +1 800 582 4263  
sales@hhp.com  
Charlotte, NC  
Tel: +1 704 998 3998  
or, in North America: +1 800 582 4263  
sales@hhp.com

**Offices Serving Europe, Middle East, and Africa**  
Europe  
Tel: +31 (0) 40 29 01 600  
euro\_sales@hhp.com  
United Kingdom  
Tel: +44 (0) 1 925 240055  
euro\_sales@hhp.com  
Italy  
Tel: +39 (0) 2 67 100752  
euro\_sales@hhp.com

France  
Tel: +33 (0) 1 41 158220  
euro\_sales@hhp.com  
Germany  
Tel: +49 (0) 7 477 151377  
euro\_sales@hhp.com  
Spain  
Tel: +34 93 228 78 68  
euro\_sales@hhp.com

**Offices Serving Asia and the Pacific Rim**  
Hong Kong  
Tel: +852 2511 3050  
asia\_sales@hhp.com  
Japan  
Tel: +813 5842 6325  
asia\_sales@hhp.com

**Offices Serving Latin America**  
Naples, Florida  
Tel: +1 239 263 7600  
la-sales@hhp.com  
São Paulo  
Tel: +55 11 5016 3454  
la-sales@hhp.com  
Rio De Janeiro  
Tel: +55 21 2494 7060  
la-sales@hhp.com

Web Site Address [www.hhp.com](http://www.hhp.com)  
Hand Held Products, Inc. d/b/a HHP ("HHP") © 1999-2003. All rights reserved. Printed in the U.S.A.  
Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.